

Absorbant Glass Mat (AGM) technology for superior performance. Valve regulated, spill proof construction allows safe operation in any position. Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified. U.L. recognized under file number MH 20567.

Maintenance-Free

Specification


Nominal Voltage	12 volts		
Nominal Capacity	77° F (25° C)		
20-hr. (0.145A)	2.9 Ah		
10-hr. (0.27A)	2.7 Ah		
5-hr. (0.5A)	2.47 Ah		
1-hr. (1.74A)	1.74 Ah		
Approximate Weight	2.59 lbs (1.18 kg)		
Internal Resistance (approx.)	15mΩ		
Max Discharge Current (7 min.)	?amperes		
Max Short-Duration Current (10 Sec.)	?amperes		
Shelf Life (% of normal capacity at 77° F (25° C))			
3 Months	6 Months	12 Months	
91%	82%	64%	
Temperature Dependency of Capacity	(20 hour rate)		
104° F	77° F	32° F	5° F
102%	100%	85%	65%



Charge Method (Constant Voltage)


Cycle Use (Repeating Use)	
Initial Current	0.87 A or smaller
Control Voltage	14.5-14.9 V
Float Use	
Control Voltage	13.5-13.8 V

Physical Dimensions: in (mm)




L: 3.11in (79 mm)
W: 2.32in (59 mm)
H: 3.90in (99 mm)
TH: 4.21in (107 mm)
 Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

Terminals




Dimension Type	L	W	w	H	T
F1	6.50	4.75	6.00	5.00	0.80

Discharge Characteristics (25° C, 68° F)




Discharge Characteristics (0° C, 32° F)




ISO 9001:2008


Shelf Life & Storage




Cycle Life vs Depth of Discharge



Open Circuit Voltage vs Residual Capacity



Effect of Temperature on Capacity



Charge Current & Final Discharge Voltage

Application	Charge Voltage(V/Cell)			Max.Charge Current	Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.30
	Temperature	Set Point	Allowable Range						
Cycle Use	25°C(77°F)	2.45	2.40-2.50	0.30C	Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C
Standby	25°C(77°F)	2.325	2.30-2.35						



Let UPG Power Your Life.

www.upgi.com